



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE

IEC 技术参数 IEC Technical Data		IEC61076-2-101	
工作温度 Operating temperatur [°C]	-25~+80	防护等级 IP Class (IN Locked condition)	IP67
额定电压 Rated Voltage [V]		额定电流 Rated Current [A]	
导线截面积 Conductor cross section		接线范围 Wire Range	
单/多芯线 Solid/Stranded [AWG]		材料 Material	
绝缘材料 Insulation Material	PA 66	阻燃等级 Imflammability	UL94V-0
导体材料 Contactor Material	铜合金 Copper alloy	导体镀层 Contactive Coating	镀金 Gold Plated
螺母/螺丝 Connector Nut/Screw	Brass With Nickel Plated 铜镀镍	符合RoHS环保要求	

Contacts Pin 数	3Pin	4Pin	5Pin	8Pin	12Pin	17Pin
A-Coding						
Rated Current 额定电流	4A	4A	4A	2A	1.5A	1.5A
Rated Voltage 额定电压	250V	250V	60V	30V	30V	30V
Wire Range 线范围	22AWG	22AWG	22AWG	24AWG	26AWG	26AWG
PART NO. 品名:	M12-A03P-ST0-M02-BQ3	M12-A04P-ST0-M02-BQ3	M12-A05P-ST0-M02-BQ3	M12-A08P-ST0-M02-BQ3	M12-A12P-ST0-M02-BQ3	M12-A17P-ST0-M02-BQ3

F	O-Ring	O-Ring FKM Black	pcs	1
E	Resin	Black epoxy resin for sealing	g	2
D	Nut	Nut: M12 X1.0, Brass With Nickel Plated	pcs	1
C	Housing	A-Coding Male, Black PA66	pcs	1
B	Terminal	Male Terminal, Brass With Gold Plated	pcs	X
A	Screw	Screw M12 X1.0, Brass With Nickel Plated	pcs	1
编号 No.	料号 Materials.No	品名 Name	材料规格 Description	单位 Unit 用量 Qty

NO SPECIFIED TOLERANCE		Cus' P/N:		Order No.: ---		Drawing No.: SP-02-M000XX	
		LINEAR	0.5-6 ±0.1	DES.	Jun	DATE	UNITS mm
	6-30 ±0.2	CHK.		DATE	SIZE A4	THIRD ANGLE PROJECTION	
	>30 ±2%	APP.		DATE	SCALE X:X	1 of 1	
ANGLES	±1°			DATE	文件等级: 外部公开		



慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD

PART NO.:
M12-AXXP-ST0-M02-BQ3